


360nm Ultraviolet DPSS Low Noise Laser



†**Specifications**

Product Code	SSL - 360 - XXXX - LN
Wavelength [nm]	360
Output Power [mW]	1 - 100
Transverse Mode	TEM ₀₀ / CW
Operating Temperature [°C]	+10 - +35
Storage Temperatures [°C]	-10 - +45
Warm-up Time [minutes]	< 15
Power Stability [rms, over 4 hours]	< 5%, < 3%, < 1%
M ² Factor	< 1.5
Beam Diameter At The Aperture [mm]	~ 1.0
Beam Divergence, Full Angle [mrad]	< 1.2
Spectral Linewidth [nm]	< 0.1
Polarization Ratio	> 100 : 1
Point Stability After Warm-up [mrad]	< 0.05
Noise of Amplitude [rms]	< 1%
Laser Head Dimensions [mm]	200 [L] × 70 [W] × 50 [H]
Power Supply Dimensions [mm]	235 [L] × 145 [W] × 100 [H]
Working Voltage [VAC]	85~245, 50/60Hz
Laser Gross Weight [kg]	3.5
Cooling Way	Cooled by TEC and air
Expected Lifetime [hours]	> 10000
Warranty Time [year]	1

Laser Head Dimension:



Power Supply Dimension:

